

THE ESSENCE OF DATA DELIVERY

promax 200 | 400



2 OR 4 DVD RECORDERS

400 DISC INPUT CAPACITY

RAPID & RELIABLE ROBOTICS

WINDOWS BASED SERVER

CHOICE OF MARKET LEADING THERMAL PRINTERS

PROGRAMMABLE API

NETWORK READY

LARGE VOLUME CD/DVD PUBLISHING SYSTEMS

CopyPro, the market leaders in automated CD/DVD publishing systems introduce the new versatile and high-performance **ProMax** range. Whether it's on-demand publishing, duplicating or printing, the **ProMax** delivers every time with first class results.

With its large 400 disc input capacity and external server, the maximum throughput for any application is achieved in a fully networked environment.

Its smooth and robust robotics exceed the demands of 24/7 production. Along with the powerful but user friendly software, high-speed recorders and top class thermal colour printers, CD/DVD production is brought to a new level.

SOFTWARE FLEXIBILITY & INTEGRATION

The **CopyPro** software suite is the most advanced and versatile on the market, allowing queuing of multiple jobs and unique disc creation with full customization options either working directly from the **ProMax** system or across the network.

When integration into custom applications is required, the **CopyPro Advanced Programming Interface (API)** makes implementation trouble-free. Job files can automatically be generated through a text editor, database program or other software applications.

The **CopyPro Hot Folder** solution is another simple, user friendly method for the submission of automatic CD/DVD production across the network. Thanks to its extensive range of settings, users can also define the role of the hot folder.

THE RIGHT PRINT SOLUTION FOR EVERY PROJECT

With the choice of two outstanding thermal printers, the **ProMax** has the flexibility to meet your demanding requirements.

Teac P55 Thermal Re-Transfer Printer

The **Teac P55** produces the finest photo quality professionally printed discs. Thanks to its innovative thermal re-transfer 4 colour print technology full colour discs can be created quickly and effortlessly. Not only does it produce an outstanding glossy finish, once printed the discs become scratchproof, UV protected and water resistant.

CopyPro PowerPro III Thermal Transfer Printer

The **PowerPro III** is ideal for on-demand monochrome printing, with exceptionally fast printing and low print costs. Once printed on white or silver discs, the label is highly durable and water resistant.

SOFTWARE FEATURES:

Queue multiple jobs

Real time job status

Create custom recorded & printed discs

Data verification

Send jobs across the network from multiple stations

Email notification

Disc label serialisation

Print or record only function

Simple label disc creation

Programmable API for third party integration

The ProMax range can enhance any business:

Medical Imaging, Photography, Data Archiving, Marketing Material, Legal Documentation, Maps & Manuals, Bureau Services, Software Distribution, Audio & Video, Banking & Financial Records.



promax 200

PRINT TECHNOLOGY

Teac P55 Thermal Re-Transfer or CopyPro PowerPro III Thermal Printer

CONFIGURATIONS

2 DVD recorders and 1 printer

DISC CAPACITY

400 disc input capacity

SUPPORTED CLIENT OPERATING SYSTEMS

Windows 2000 & XP

SUPPORTED HOST OPERATING SYSTEMS

Windows 2000 & XP

SYSTEM REQUIREMENTS

Dell PowerEdge Server control centre included.

SOFTWARE

ProMax Software Suite
Copypro API (Optional)

NETWORK READY

Yes

PHYSICAL DIMENSIONS

H57cm x W37cm x D68cm

WEIGHT

Loader - 28kg
Teac P55 - 22kg
PowerPro III - 14kg

INTERFACE

USB 2.0

POWER

100-240V AC, 50/60 Hz
500W Max

CERTIFICATIONS

CE, RoHS



promax 400

PRINT TECHNOLOGY

Teac P55 Thermal Re-Transfer or CopyPro PowerPro III Thermal Printer

CONFIGURATIONS

4 DVD recorders and 1 printer

DISC CAPACITY

400 disc input capacity

SUPPORTED CLIENT OPERATING SYSTEMS

Windows 2000 & XP

SUPPORTED HOST OPERATING SYSTEMS

Windows 2000 & XP

SYSTEM REQUIREMENTS

Dell PowerEdge Server control centre included.

SOFTWARE

ProMax Software Suite
Copypro API (Optional)

NETWORK READY

Yes

PHYSICAL DIMENSIONS

H57cm x W37cm x D68cm

WEIGHT

Loader - 29.5kg
Teac P55 - 22kg
PowerPro III - 14kg

INTERFACE

USB 2.0

POWER

100-240V AC, 50/60 Hz
500W Max

CERTIFICATIONS

CE, RoHS